



GLORystAR

MAGNETAR Weatherproof Touch Screen



IP65 Front Glass



1000 nits brightness



Fingerprint & Scratch Resistant

Overview

The Glory Star Magnetar Weatherproof Touch Screen is IP65 rated, dust and water resistant in the front glass. Equipped with a high brightness screen, fingerprint and scratch resistance surface makes it a true industrial grade solution. It is cost effective for system integrators who require a reliable product for indoor and outdoor applications.

Designed with reliability from the start, Glory Star's Magnetar weatherproof touch screen delivers seamless and accurate touch response with a 6H scratch resistant touch glass, that is enough to withstand demanding applications, making these products very suitable for use in public environments.

WINDOWS PLATFORM

Processors		J6412			i3- 8145U			i5 8265U		
Model Number		MAG101 Part#J6412	MAG156 Part#J6412	MAG156 Part#J6412	MAG101 Part#8145U	MAG156 Part#8145U	MAG156 Part#8145U	MAG215 Part#8265U	MAG215 Part#8265U	MAG215 Part#8265U
Screen Size		10"	15.6"	21.5"	10"	15.6"	21.5"	10"	15.6"	21.5"
Panel Info	Resolution	1280x 800	1920 x 1080	1920 x 1080	1280x 800	1920 x 1080	1920 x 1080	1280x 800	1920 x 1080	1920 x 1080
	Brightness	1000cd/m2								
	Contrast Ratio	1300:1	1000:1	5000:1	1300:1	1000:1	5000:1	1300:1	1000:1	5000:1
	Aspect Ratio	16:10	16:9	16:9	16:10	16:9	16:9	16:10	16:9	16:9
	Active Display Area (mm)	216.96x135.6	344.16x193.59	476.64 x 268.11	216.96 x 135.6	344.16 x 193.59	476.64x268.11	216.96x135.6	344.16x 193.59	476.64x268.11
	Viewing Angle	85°/85° /85°/85	89°/89° /89°/89°	89°/89° /89°/89°	85°/85° /85°/85°	89°/89° /89°/89°	89°/89° /89°/89°	85°/85° /85°/85°	89°/89° /89°/89°	89°/89° /89°/89°
	Touch Tech	G+G Capacitive Touch 10pt IP65 Rating Optical bonded capacitive touch (touch on water or latex glove) UV Protection								
CPU& System	CPU	J6412			i3-8145U			i5-8265U		
	Base Frequency	2.0GHz			2.1GHz			1.6GHz		
	CPU Turbo Boost	2.6GHz			3.9GHz			3.9GHz		
	CPU Cache	1.5MB			4MB			6MB		
	BIOS	AMI 16MB UEFI BIOS								
RAM	RAM	8GB , Single Channel SO-DIMM DDR4 (Max 32GB)			8GB , Dual Channel 2 x DDR4 2400MHz (Max 32GB)					
ROM	Storages	For 10inch M.2 - 2280 256GB SSD For 15 and 21inch SATA3.0 256GB SSD								
Software	OS	Window 10 IoT Enterprise LTSC 2019 english version 64 bit), Linux 32 / 64 bit								
Display	GPU Chipset	Intel® UHD Graphics for 10th Gen			Intel® HD Graphics 610/620 (Based on CPU)					
	Display Port	DP 1.4			DP.1.2					
	HDMI	1 x HDMI 2.0			1x HDMI 1.4					
Audio	Speaker	3WX 2								
Ethernet	Controller	RTL8111H – 10/100/1000Mbps			Intel i211/i219 – 10/100/1000Mbps					
	Connector	2 x RJ45								
	Wake on Lan	Yes								
	WIFI/ Bluetooth	IEEE 802.11a/b/n/ac, Wi-Fi compliant , Bluetooth 4.0								
Storage	Slot	For 10inch : 1x M.2 for 2280 SSD For 15 and 21inch : 2x SATA3.0(only 1 SATA3.0 for J6412)								
Housing	Material & Color	Metal Outdoor Housing with Black Matte Paint								
	Chassis	IP65 front IPX2 rear								
	Front	IP65								
	Back	IPX2								
Rear Panel I/O	USB 2.0	N/A			1xUSB 2.0			1xUSB 2.0		
	USB 3.0	J6412: 4xUSB 3.0			3xUSB 3.0			3xUSB 3.0		
	Audio	Line-out x 1; Mic-in x 1								
	LAN	2(10/100/1000Mbps)								
	HDMI	(HDMI1.4) x 1								
	Display Port	(DP1.2) x 1								
Insider PCBA	COM	5 x RS232 / 1 x RS485 (inside PCBA)								
	USB 2.0	3 x USB2.0 header (inside PCBA)								
	I/O	8 x GPIO (inside PCBA)								
	PS/2	1 x PS2_H (inside PCBA)								
	LPT	1 x LPT (inside PCBA)								
Power	Standard Port	1 x 12V DC-IN								
Hardware Monitor	Sensor	Voltage sensor; Watchdog; Plug and Start								
	Included in Box	MAGNETAR tablet, Power Adaptor, Power cable								
	Consumption									
	Power Adaptor	DC 12V 5A	DC 12V 7.5A		DC 12V 5A	DC 12V 7.5A		DC 12V 5A	DC 12V 7.5A	
	Operating Environment	-30°C—65°C								
	Language	Multi language								
	VESA	VESA 100								
Power Adaptor	Input	AC 100-240V, 50/60Hz								
Dimensions	Size (WxDxH)	10 inch: 278.56×197.2×40.8mm			15.6 inch: 389.45×238.74×45.8mm			21.5 inch: 523.9×315.4×46.3mm		
Product Weight										
Gift Box Size		10 inch : 396 x 241 x 86 mm			15.6inch: 443 x 115 x 303 mm			21.5inch: 583 x 115 x 382mm		
Master Carton Size		10inch : 506x 410 x 288mm			15.6inch: 464 x 365 x 327mm			21.5inch: 604 x 248 x 406mm		
Master Carton Weight										
Units per Master Carton		10inch: 6pcs 15.6inch: 3pcs 21.5inch: 2 pcs								

ANDROID PLATFORM

	Model	MAG101 Part#CT399	MAG156 Part#CT399	MAG215 Part#CT399
Screen Size	Size	10"	15.6"	21.5"
	Resolution	1280x 800	1920 x 1080	1920 x 1080
	Brightness	1000cd/m2		
	Contrast	1300:1	1000:1	5000:1
	Aspect Ratio	16:10	16:9	16:9
	Active Display Area	216.96 x 135.6mm	344.16 x 193.59mm	476.64 x 268.11 mm
	Viewing Angle	85°/85°/85°/85°	89°/89°/89°/89°	89°/89°/89°/89°
	Touch Tech	G+G Capacitive Touch 10pt IP65 Rating Optical bonded capacitive touch (touch on water or latex glove) UV Protection		
Hardware & OS	CPU	RK3399 Hexa Core Dual core Cortex-A72 up to 1.8GHz, Quad core Cortex-A53 up to 1.4GHz		
	RAM	4GB LPDDR4		
	ROM	32GB EMMC		
	OS	Android 9 Upgradable to Android 12		
Software	STAROS	License Free STAROS Kiosk Lockdown App included		
	STARCONTROL	Star Control Remote Device Monitoring Free 3 months Trial		
	STARTOOL	Tool for developers to control device and Open API		
Video/ Image	Video Format	MOV, FLV, MP4, MKV, MPG, MPEG, etc		
	Audio Format	AAC, AMR, FLAC, M4A, M4R, MP2, MP3, OGG, WAV, WMA, etc.		
	Image Format	JPG, BMP, PNG, GIF, etc		
Audio	Speaker	2W x2		
Communication	Bluetooth	BT 5.0		
	WIFI	802.11 b/g/n 2.4GHz and 5GHz		
	Ethernet	1 x RJ45, 100/1000 LAN		
General	Color	Metal Outdoor Housing with Black Matte Paint		
	Chasis	IP65 front IPX2 rear		
	I/O	DC IN x1; Audio out x1; HDMI x1; USB2.0x1; USB3.0x1; TYPE-C OTGx1; TF CARDx1; RJ45x1; GPIOx1 GPIO: 1xUART1; 2xGPIO; 1xWiegand; 1xVCC-5V		
	POE	N/A		
	Included in Box	MAGNETAR tablet, Power Adaptor, Power cable		
	Sensors	1 x Light and Distance Sensor		
	Consumption	18W	36W	36W
Power Input	DC 12V 1.5A	DC 12V 3A	DC 12V 5A	
Operating Environment	-30°C—65°C			
Language	Multi language			
	VESA	VESA 100		
Dimensions	Dimensions (LxWXH)	278.56×197.2×36.8mm	389.45×238.74×40.8mm	523.7×315.18×41.68mm
	Weight	2.1kg	3.43kg	5.9kg
	Box size / each pc (LxWXH)	396×241×86mm	443 x 115 x 303mm	583 x 115 x 382mm
	Master Box size (LxWXH)	506×410×288mm	464 x 365 x 327mm	604 x 248 x 406mm
	Master Box Weight			
	Pieces/ Carton	6pcs	3pcs	2pcs

CONTACT US

United States

1440 N. Harbor Blvd Suite 900
Fullerton, CA 92835, USA
[626 228 5927](tel:6262285927)

Hong Kong

Flat D, 5/F, Excelsior Building,
364 Nathan Road,
Kowloon, Hong Kong
[852 23762803](tel:85223762803)

ShenZhen

Bldg 9, 4/F Zhong Yuntai Technology Industrial Park,
Tangtou No.1 Road, Shiyan Street, Baoan,
ShenZhen, PRC
[86 755 2600 1808](tel:8675526001808)

To find out more about our extensive range of Glory Star solutions, go to www.glorystargroup.com, or call the office nearest you. For more information, please contact us at sales@glorystargroup.com. Glory Star reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glory Star, the Glory Star logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glory StarGroup Limited. All other trademarks are the property of their respective owners.