



STH-500



HTS-500

Features

- Input : Embedded 3G/HD/SD-SDI
- Output : HDMI
- HDMI V1.3 standards
- SDI loop through output
- Upload and configuration via USB2.0

Specification

Video Input

Digital Input	3G/HD/SD-SDI
Resolutions	480i(29.9/30), 576i(25), 720p(50/59.94/60) 1080i(25/29.97/30) 1080p(23.98/24/25/29.97/30/50/59.94/60)
Impedance	75Ω
Aspect Ratio	4:3, 16:9

Audio Input

Digital Input	Embedded SDI
Sampling Rate	48KHz
Connector	BNC (75Ω)

SDI

Compliance	SMPTE-259/272/274/292/296/299/424/425
Data Rates	SD-SDI : 270Mbps HD-SDI : 1.5Gb/s & 3Gb/s
Video Rates	4:2:2, 4:4:4
Color Space	YUV

HDMI

Color Precision	4:2:2, 4:4:4
Version	V1.3 Standard

Video Output

Digital Output	HDMI
Aspect Ratio	4:3, 16:9

General

Power Requirements	DC 12V Weight 0.22Kg
Dimensions	110x90x28 mm

Features

- Input : HDMI
- Output: 3G/HD/SD-SDI
- HDMI V1.3 standards
- Upload and configuration via USB2.0

Specification

Video Input

Digital Input	HDMI
Resolutions	480i(29.9/30), 576i(25), 720p(50/59.94/60) 1080i(25/29.97/30) 1080p(23.98/24/25/29.97/30/50/59.94/60)
Aspect Ratio	4:3, 16:9

Audio Input

Digital Input	Embedded HDMI
Sampling Rate	32,44.1,48KHz
Connector	HDMI-19PIN

SDI

Compliance	SMPTE-259/272/274/292/296/299/424/425
Data Rates	SD-SDI : 270Mbps HD-SDI : 1.5Gb/s & 3Gb/s
Video Rates	4:2:2, 4:4:4
Color Space	YUV

HDMI

Color Precision	4:2:2, 4:4:4
Version	V1.3 Standard

Video Output

Digital Output	3G/HD/SD-SDI
Impedance	75 Ω
Aspect Ratio	4:3, 16:9

General

Power Requirements	DC 12V Weight 0.22Kg
Dimensions	110x90x28 mm

