



GLORYSTAR

VEGA X Gen 2 Access Control



Identify & track via RFID



Micro USB Updates



API third party integration

Overview

Glory Star's Vega X is an IP65 waterproof outdoor access control device that supports SIP with IP calling. Running on an Android operating system, it offers third-party software developers and system integrators the ability to develop their software and services on top of Vega X and VegaOS. Private label services are also available, in addition to selling and supporting Vega X. This device is specifically designed for gate entrances, commercial and residential building entrances. Glory Star's open API combined with the Android platform has created a low barrier to entry, resulting in a high ROI for software developers and system integrators.

Echo-Canceling

Proximity Sensor

RFID

IP65 Waterproof & Anti-Glare tempered glass

Reduce Installation cost

Ambient Sensor

POE

	Model	VOD073 Part# CT568	
Screen Size	Size	7"	
Panel Info	Resolution	1280 x 800	
	Brightness	400cdm2	
	Contrast	800:1	
	Aspect Ratio	16:10	
	Active Display Area	149.76 x 93.60mm	
	Viewing Angle	88°/88°/88°/88°	
	Touch Tech	10 point cap touch	
Hardware & OS	CPU	Quad Core Cortex A55 up to 2.0GHz 1TOPSNPU	
	RAM	4GB DDR4	
	ROM	32GB eMMC Flash	
	OS	Android 12	
Software	STAROS	License Free STAROS Kiosk Lockdown App included	
	STAR CONTROL	Star Control Remote Device Monitoring Free 3 months Trial	
	STARTOOL	Tool for developers to control device and Open API	
Video/ Image	Video Format	MOV, FLV, MP4, MKV, MPG, VOB, AVI, WMV, etc.	
	Audio Format	WMA, WAV,AAC, FLAC, MID,APE, MP2, LRC, M4A, MP1, MP3, etc.	
	Image Format	JPG, BMP, PNG, GIF, etc.	
Audio	Speaker	1 x 2W	
	Camera	200W HDR Camera	
Communication	Bluetooth	BT 5.0	
WIFI	WIFI	802.11 a/b/g/n/ac 2.4GHz + 5GHz	
	Ethernet	10/100	
General	Color	Black	
	Chassis	Plastic	
	I/O	INPUT x 2, Wiegand x1, RS485 x 1, Relay x 2	
	POE	IEEE802.3af standard	
	Included in Box	Tablet	
	Sensors	Proximity Sensor, Ambient Sensor	
	Consumption	13W	
	Power Input	Either 12V DC or POE	
	Operating Environment		Operating Temperature: 32° - 104°F (0° - 40°C) Storage Temperature: -4° - 122°F (-20° - 50°C) Working Humidity: 20% -80% Storage Humidity: 10% - 95%
		Language	Multi Language
Mounting	VESA	N/A	
	Dimensions	262.51 x 126.51 x 31.9mm	
Dimensions	Dimensions (LxWXH)		
	Weight	0.9Kg	
	Box size / each pc (LxWXH)	405 x 208 x 127 mm	
	Master Box size (LXWXH)	440 x 420 x 405	
	Master Box Weight	8.4Kg (without bracket)	
	Pieces/ Carton	6pcs	

CONTACT US

United States

1440 N. Harbor Blvd Suite 900
Fullerton, CA 92835, USA
[626 228 5927](tel:6262285927)

Hong Kong

Flat D, 5/F, Excelsior Building,
364 Nathan Road,
Kowloon, Hong Kong
[852 23762803](tel:85223762803)

ShenZhen

Bldg. 9, 4/F Zhong Yuntai Technology Industrial
Park, Tangtou No.1 Road, Shiyan Street, Baoan,
ShenZhen, PRC
[86 755 2600 1808](tel:8675526001808)

To find out more about our extensive range of Glory Star solutions, go to www.glorystargroup.com, or call the office nearest you. For more information, please contact us at sales@glorystargroup.com. Glory Star reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glory Star, the Glory Star logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glory Star Group Limited. All other trademarks are the property of their respective owners.